

This walk-up, through-the-wall ATM is designed for high-traffic areas with the capacity to hold up to 6,000 notes. Plus, it offers true flexibility for future expansion.

Features

Powerful Transaction Support

With the Microsoft Windows XP Platform and an Intel Pentium Processor, the Monimax 7000T guarantees support for both larger and faster transactions.

High Level of Scalability.

Designed to support multi-vendor solutions, this ATM can easily support additional financial services, including an optional built-in check scanner, bill acceptor and envelope depository.

Reliability

The Monimax 7000T satisfies demanding performance standards such as UL 291Level 1 and PCI-certified encrypting PIN pad.

Convenient Side-access Design

Both side- and rear-access make it easier to load cassettes, provide service and minimize downtime.

Superior quality, security and value.

Only with Nautilus Hyosung.

Now offering the most complete line of financial and retail ATMs.



The Monimax 7000T offers a customer-centric interface with the power to grow with your business.

Dependable Customer Service

You can't afford ATM downtime. That's why we offer customer service with real people and real solutions. Trust Nautilus Hyosung to be your business partner.

MONIMAX 7000T

System Control

- Embedded Microsoft® Windows XP® platform
- Intel® Pentium®-IV processor

Customer Display

- 10.4" TFT LCD
- Sunlight viewable

Communication

- TCP/IP (SSL configurable)

Input Type

- 4 x 2 function keys
- Optional touch screen
- 4 x 4 numeric keys
- PCI EPP (Encrypting PIN pad)
- ADA compliant

Supervisor Operation

- 15" TFT LCD

Card Handling

- Dip-type card reader
- Optional IC card reader, EMV Level 1, 2

Cash Dispensing

- Two cassettes
- Optional cassettes (up to three)

Depository

- Envelope depository

Printers

- 3.1" graphical thermal receipt printer
- Electronic journal
- Optional journal printer

Security

- UL291 Level 1 safe
- Mechanical combination lock
- Optional electronic safe lock
- Optional KABA Mas Cencon safe lock

Miscellaneous

- Heater
- Lead-through indicator
- Illuminated signage

Power Supply

- AC 110–230V, 50–60 Hz

Operating Environment

- Temperature: -31°F–104°F
- Humidity: 25%–86%

Dimension and Weight

- Height: 61.2" (1,548 mm)
- Width: 32.6" (830 mm)
- Depth: 38.6" (982 mm)
- Weight: 1,440 lbs (650 kg)

Internal components may change with the introduction of new technology. Nautilus Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.



Nautilus
HYOSUNG

Contact your authorized Nautilus Hyosung distributor or representative for more information.